

Change Added/ Deleted/ Modified	Domains	Regulatory activity	Content of the Regulation	Regulatory organisation	Target date for regulatory material publication	EASA UAS categories	Status	Standardisation activity	Short description of the deliverable	SDO	Target date for publication	Type of document (standard, supporting material etc.)	Status	Comments
General														
M	Definition and classification							AS6969	This data dictionary provides a mathematically coherent set of definitions for quantity types used in data models for unmanned systems. In this data dictionary, a quantity is defined as a property of a phenomenon, substance, or body whose value has magnitude.	SAE AS-4UCS Unmanned Systems (Xs) Control Segment Architecture	Jun-18	standard	ongoing	
	Definition and classification							AR6128 Unmanned Systems Terminology Based on the ALFUS Framework	This SAE Aerospace Recommended Practice (ARP) describes terminology specific to unmanned systems (UMSs) and definitions for those terms. It focuses only on terms used exclusively for the development, testing, and other activities regarding UMSs. Terms that are used in the community but can be understood with common dictionary definitions are not included in this document. Further efforts to expand the scope of the terminology are being planned.	SAE AS-4JAU Joint Architecture for Unmanned Systems Committee		recommended practice	published	
	Definition and classification							AS#### UAS Propulsion System Terminology		SAE E-39 Unmanned Aircraft Propulsion Committee	May-19	standard	planned	
	Definition and classification							ASTM WK62416 New Standard Terminology for Unmanned Aircraft Systems	Develop a standard that presents a lexicon for unmanned aircraft systems (UAS). The Standard Terminology for Unmanned Aircraft Systems ("Standard Terminology") is designed to support the global UAS community, a community that includes both traditional manned aviators and new UAS aviators who are unfamiliar with aviation safety culture, practices, and regulations. This terminology contains a listing of terms, abbreviations, acronyms, and symbols related to UAS. It is intended to ensure the consistent use of terminology for the UAS community throughout all unmanned aircraft standards.	ASTM F38 Unmanned Aircraft Systems	Jan-19		planned	Under development. A new description of the deliverable
	Definition and classification							ISO 21895 - Requirements for the categorization and classification of civil UAS. The standard applies to their industrial regulation, development and production, delivery and usage.		ISO TC20/SC16/WG1	Dec-18	standard	ongoing	
	Definition and classification							ISO 21384-1 - General requirements for UAS for civil and commercial applications, UAS terminology and classification	Provides the foundation and common terms, definitions and references relevant to the whole Standard, the purpose of which is to provide a safety quality standard for the safe operation of all UAS through the provision of synergistic standards for manufacturing and operations.	ISO TC20/SC16/WG1	Dec-18	standard	ongoing	
A	Definition and classification							ASTM WK62744 General Operations Manual for Professional Operator of Light Unmanned Aircraft Systems (UAS)	This standard defines the requirements for General Operations Manual for Professional Operator of Light Unmanned Aircraft Systems (UAS). The standard addresses the requirements and/or best practices for documentation and organization of a professional operator (i.e., for compensation and hire). The intent is for this standard to support professional entities that will receive operator certification by a CAA, and provide standards of practice for self- or third-party audit of operators of UAS. Not all CAAs have operator certificates. This would provide a standard for operators and identify gaps that are not currently addressed as it relates to: (1) Individuals, who are currently remote pilots (i.e. FAA under Part 107) in jurisdictions that do not separately certify Operators, who want to voluntarily comply with a higher standard, and (2) Operators, who are seeking certification from a CAA for Light Unmanned Aircraft Systems, who want to voluntarily comply with an industry standard (3) Public agencies interested in developing unmanned aircraft systems programs.	ASTM F38 Unmanned Aircraft Systems	Mar-19	standard	ongoing	
A	Manuals							ASTM WK62743 Development of Maintenance Manual for Small UAS	This specification provides the minimum requirements for a General Maintenance Manual (GMM) for an unmanned aircraft system (UAS) designed, manufactured, and operated in the small UAS category as defined by a Civil Aviation Authority (CAA).	ASTM F38 Unmanned Aircraft Systems	Jan-19	standard	ongoing	In subcommittee for vote
	Manuals	Opinion No.1 2018	Appendix 2, 3, 4, UAS in class C1, C2 and C3 shall be placed on the market with a user's manual providing the characteristics of the UA (including but not limited to the mass of the UA, the MTOM, including its payload, the frequency of the electronic identification emission, the general characteristics of allowed payloads in terms of mass and dimensions, a description of the behaviour of the UA in case of a loss of data link), clear operational instructions, troubleshooting procedures, and operational limitations (including but not limited to meteorological conditions and daylight operations) as well as an appropriate description of all the risks related to UAS operations;	EASA	Mar-19	open	Opinion published							
	Manuals	Opinion No.1 2018	Appendix 1 to delegated act UAS in class C0 shall be placed on the market with clear operational instructions and warnings highlighting the risks related to UAS operations, which shall be adapted to the age of the user;	EASA	Mar-19	open	Opinion published							Process Standard - specifies generic methods, which are not specific to individual components, e.g. software or hardware development, environmental testing
	Manuals	Opinion No.1 2018	Appendix 5to delegated act UAS in class C4 shall be placed on the market with a user's manual providing the characteristics of the UA (including but not limited to the mass of the UA and its MTOM, including its payload, and a description of the behaviour of the UA in case of a loss of data link), clear operational instructions and operational limitations (including but not limited to meteorological conditions and daylight operations) as well as an appropriate description of all the risks related to UAS operations;	EASA	Mar-19	open	Opinion published							Minimum Operational Performance Standard (MOPS) - specifies the performance of a component (piece of equipment, protocols, exchange formats, ...), which is the minimum necessary performance to satisfy a regulatory requirement. In particular, it specifies the tests to be made to ensure that the specified performance is achieved.
	Manuals	Opinion No.1 2018	Appendix 1, 2, 3, 4, to delegated act UAS in class C0, c1, C2, and C3 shall be safely controllable by a remote pilot following the manufacturer's instructions;	EASA	Mar-19	open	Opinion published							Technical Standard - specifies performance of a component, which reflects the best industrial practice.
	Definition and classification	Opinion No.1 2018	Appendix 2, 3, 4, 6to delegated act UAS in class C1, C2, C3 and E-ID add on shall have a unique serial number that must be affixed in a legible manner on the UA and the packaging or the user's manual;	EASA	Mar-19	open	Opinion published							Guidance Document - supplements the information contained in the types of documents described above. Usually illustrative information to another EUROCAE document.
	Definition and classification							ANSI/CTA - 2063 Small Unmanned Aerial Systems Serial Numbers	This standard outlines the elements and characteristics of a serial number to be used by small unmanned aerial systems.	CTA RE Portable Handheld and In-Vehicle Electronics Committee WG 23 Unmanned Aerial Systems		standard	published	Internal Report - represents the opinion of a WG on a certain technical topic. It is identified with a WG reference number and date only.
	Definition and classification	EASA Decision	050W23 Environmental conditions for safe operations defined, measurable and adhered to (<u>Criterion #1 Definition</u>)	EASA	May-19	Specific	ongoing							
	Operator organisations	EASA Decision	050W1 Ensure the operator is competent and/or proven	EASA	May-19	Specific	ongoing							EUROCONTROL Specifications - Define technical and/or operational procedures that advance ATM

Version: 2.0 28/09/2018

ASTM

- Test method** - a definitive procedure that produces a test result.
- Guide** - information or series of options that does not recommend a specific course of action.
- Practice** - a definitive set of instructions for performing one or more specific operations that does not produce a test result.
- Classification** - a systematic arrangement or division of materials, products, systems, or services into groups based on similar characteristics such as origin, composition, properties, or use.
- Terminology** - a document comprising definitions of terms; explanations of symbols, abbreviations, or acronyms.

EUROCAE

- Minimum Aviation Systems Performance Standards (MASPS)** - describes and specifies the operational and/or functional requirements of a complete end-to-end system, which may include airborne, on-ground and space segments. It should provide a high-level architecture describing the individual components, and should allocate between those components the performance, safety and interoperability requirements.
- Operational Services and Environment Definition (OSED)** - a document dedicated to the operational concept description: it provides the definition of the considered services and of the environment, in which they have to be provided. It is usually published as an annex to the SPR.

Safety and Performance Requirements Standard (SPR) - a standalone document dedicated to operational safety and performance issues: it provides an allocation of the requirements between the segments for the different approval types.

Interoperability requirements standard (INTEROP) - a standalone document dedicated to interoperability issues between the different segments: for each of them, it identifies the technical interface and related functional requirements

Process Standard - specifies generic methods, which are not specific to individual components, e.g. software or hardware development, environmental testing

Minimum Operational Performance Standard (MOPS) - specifies the performance of a component (piece of equipment, protocols, exchange formats, ...), which is the minimum necessary performance to satisfy a regulatory requirement. In particular, it specifies the tests to be made to ensure that the specified performance is achieved.

Technical Standard - specifies performance of a component, which reflects the best industrial practice.

Guidance Document - supplements the information contained in the types of documents described above. Usually illustrative information to another EUROCAE document.

Internal Report - represents the opinion of a WG on a certain technical topic. It is identified with a WG reference number and date only.

EUROCONTROL Specifications - Define technical and/or operational procedures that advance ATM

	manufacturer organisation	EASA Decision	OSD#2 UAS manufactured by competent and/or proven entity	EASA	May-19	Specific	ongoing													
	Maintenance organisation	EASA Decision	OSD#3 UAS maintained by competent and/or proven entity (e.g. industry standards). (Criterion #1 Procedures)	EASA	May-19	Specific	ongoing													
	Maintenance organisation	EASA Decision	OSD#3 UAS maintained by competent and/or proven entity (e.g. industry standards). (Criterion #2 Training)	EASA	May-19	Specific	ongoing													
	service provider	EASA Decision	OSO #13 - External services supporting UAS operations are adequate to the operation	EASA	May-19	Specific	ongoing													
	Operator organisations	EASA Decision	OSO #07 - Inspection of the UAS (product inspection) to ensure consistency to the ConOps	EASA	May-19	Specific	ongoing													
	Operator organisations	EASA Decision	OSO #08 - Operational procedures are defined, validated and adhered to (to address technical issues with the UAS). Criteria 1, 2,3	EASA	May-19	Specific	ongoing													
	Operator organisations	EASA Decision	OSO #11 - Procedures are in-place to handle the deterioration of external systems supporting UAS operation: Criteria 1, 2,3	EASA	May-19	Specific	ongoing													
	Operator organisations	EASA Decision	OSO #14 - Operational procedures are defined, validated and adhered to (to address Human Errors): Criteria 1, 2,3	EASA	May-19	Specific	ongoing													
	Operator organisations	EASA Decision	OSO #21 - Operational procedures are defined, validated and adhered to (to address Adverse Operating Conditions): Criteria 1, 2,3	EASA	May-19	Specific	ongoing													
	Operator organisations	EASA Decision	OSD#19 Safe recovery from Human Error (Criterion #1 Procedures and checklists)	EASA	May-19	Specific	ongoing													
	Operator organisations	EASA Decision	OSD#16 Multi crew coordination. (Criterion #1 Procedures)	EASA	May-19	Specific	ongoing													
	Operator organisations	EASA Decision	OSD#23 Environmental conditions for safe operations defined, measurable and adhered to (Criterion #1 Procedures)	EASA	May-19	Specific	ongoing													
	Operator organisations	EASA Decision	M#1 An Emergency Response Plan (ERP) is in place, operator validated and effective (Criterion #1 Operational)	EASA	May-19	Specific	ongoing													
2	UAS Traffic Management																			
	U-space	TBD	Network E-identification. It is linked to the U-Space	EASA	TBD	Open category and Specific														
	Electronic Identification						MASPS for UAS e-identification	"Minimum Aviation Systems Performance Standard for UAS e-identification" defining minimum system level end-to-end requirements for the implementation of the electronic identification function for UAS.	EUROCAE WG-105	Nov-18	standard	ongoing								
	Electronic Identification						MOPS for UAS e-identification	"Minimum Operational Performance Standard for UAS e-identification" defining minimum requirements for the e-identification function at the level of individual components.	EUROCAE WG-105	Jun-19	standard	planned								
M	U-space						ASTM WK63418 Protocol for UAS Provided under UAS Traffic Management (UTM)	Develop minimum requirements ensuring deconfliction of routes in the same operating region and develop industry agreed protocols that would promote the interchange and use of data between USSs (UAS Service Suppliers) to enable aircraft separation in the same region. These protocols will enable safe and efficient low-altitude airspace operations by providing services such as airspace design, corridors, dynamic geofencing, severe weather and wind avoidance, congestion management, terrain avoidance, route planning and re-routing, separation management, sequencing and spacing, and contingency management.	ASTM F38 Unmanned Aircraft Systems	TBD	standard	planned	Terms of Reference under development. Working group formed							
M	U-space						ASTM WK27055 New Practice for UAS Remote ID and Tracking	Identify the requirements and data transmission protocols for meeting the security and public safety needs of the law enforcement, homeland defence and national security communities for the remote identification and tracking of UAS. Evaluate the need to provide information that could assist in threat discrimination and determination of hostile intent. Will also inform requirement for civil and commercial operators to ensure appropriate compliance with regulation.	ASTM F38 Unmanned Aircraft Systems	TBD	standard	planned	Terms of reference under development. Working group forming. Change in description							
	U-space						AIR6388 Remote Identification and Interrogation of Unmanned Aerial Systems	The information presented in this AIR is intended to provide information about current remote identification methods and practical considerations for remotely identifying UAS. Depending on rigor and adherence requirements, Aerospace Standard (AS) and Aerospace Recommended Practice (ARP) documents may be developed. For example, ARPs may provide methods to remotely identify UAS using existing hardware technologies typically available to most consumers. ARPs may also specify the information exchange and message format between unmanned aerial systems and remote interrogation instruments. An AS, however, may highlight the wireless frequency band, message type, message encoding bits, and message contents.	SAE AS-4UCS Unmanned Systems (UAS) Control Segment Architecture	Dec-18	information report	ongoing								
M	U-space						ASTERIX Category 129 UAS Identification Reports	Defines a message structure allowing transmitting the identification of a UAS as well as its the aircraft's current position. This data is required in order to establish the basic principles of UTM (UAS Traffic Management) which shall enable the safe integration of UAS into non-segregated airspace	EUROCONTROL	Apr-18	standard	published								

Guidelines - Provide more general implementation support to stakeholders.

NOTE: Standards are developed and maintained as both harmonising standards and as means of compliance. Standards are used as reference material by ICAO and EASA, and continue to provide the basis of Community Specifications for the extant EU SES regulations in accordance with regulation EC 552/2004 (Interoperability Regulation).

ISO

International Standard - provides rules, guidelines or characteristics for activities or for their results, aimed at achieving the optimum degree of order in a given context. It can take many forms. Apart from product standards, other examples include : test methods, code of practice, guideline standards and management systems standards.

Technical Specification - addresses work still under technical development, or where it is believed that there will be a future, but not immediate, possibility of agreement on an International Standard. A Technical Specification is published for immediate use, but it also provides a means to obtain feedback. The aim is that it will eventually be transformed and republished as an International Standard.

Technical Report - contains information of a different kind from that of the previous two publications. It may include data obtained from a survey, for example, or from an informative report, or information of the perceived "state of the art".

Publicly Available Specification - is published to respond to an urgent market need, representing either the consensus of the experts within a working group, or a consensus in an organization external to ISO. As with Technical Specifications, Publicly Available Specifications are published for immediate use and also serve as a means to obtain feedback for an eventual transformation into an International Standard. Publicly Available Specifications have a maximum life of six years, after which they can be transformed into an International Standard or withdrawn.

International Workshop Agreement - is a document developed outside the normal ISO committee system to enable market players to negotiate in an "open workshop" environment. International Workshop Agreements are typically administratively supported by a member body. The published agreement includes an indication of the participating organizations involved in its development. An International Workshop Agreement has a maximum lifespan of six years, after which it can be either transformed into another ISO deliverable or is automatically withdrawn.

Guides - help readers understand more about the main areas where standards add value. Some Guides talk about how, and why, ISO standards can make it work better, safer, and more efficiently.

SAE

Standards - these Technical Reports are a documentation of broadly accepted engineering practices or specifications for a material, product, process, procedure or test method.

Recommended Practices - these Technical Reports are documentations of practice, procedures and technology that are intended as guides to standard engineering practice. Their content may be of a more general nature, or they may propound data that have not yet gained broad acceptance.

Information Reports - these Technical Reports are compilations of engineering reference data or educational material useful to the technical community.

Aerospace Material Specifications - these Technical Reports identify material and process specifications conforming to sound, established engineering and metallurgical practices in aerospace sciences and practices.

	Local E-identification	Opinion No.1/2018	Appendix 2,3,4,6 to Delegated Act A UAS Class C1, C2 and C3 and a add-on module shall: An electronic identification shall: 1. allow the user to insert the 10-digit UAS operator registration number; 2. provide in real time during the whole duration of the flight the following information through electronic data: (a) the UAS operator registration number; (b) the unique serial number of the add-on; (c) the geographical position of the UA, its height and associated time; and (d) the geographical position of the UA take-off point; 3. the information shall be protected against unauthorised modification.	EASA	Mar-19	open category and specific	Opinion published											
	Marking and Registration	Opinion No.1/2018	UAS.OPEN.060 3. UAS operator shall display the registration information on the UA. AMC: The registration number should be stated on a fire-resistant placard; a QR code (Quick Response Code) may be an acceptable means.	EASA	Mar-19	Open category and Specific	Opinion published											
	Marking and Registration							ASTM F2851-10 Standard Practice for UAS Registration and Marking (Excluding Small Unmanned Aircraft Systems)	This practice follows ICAO Annex 7 SARPS except in areas where the unique aspects of UAS may not allow compliance. In these cases, this document will address the issue and recommend the need for an alternate compliance method.	ASTM F38 Unmanned Aircraft Systems		standard	published				Ballotting for renewal	
	Marking and Registration	Opinion No.1/2018	Art 7: Each registered UAS operator shall obtain a registration number according to the format defined by EASA. AMC1 Article 7 Registration number The registration number should consist of 10 digits organised as the following: — 2 digits representing the nation; — 1 digit identifying the national register (if the nation defines multiple registers); and — 7 digits uniquely identifying the operator. UAS.OPEN.060 and UAS.Spec.060 Registration 2. update their registration every time data is changed and renew the registration as required by the competent authority; AMC1 UAS.OPEN.060(1) and UAS.SPEC.060(1) Registration form 1. The UAS operator should complete the registration process online and provide at least their: (a) Full name or the name of the business, if a company; (b) mailing address where the operator is established or residing; (c) email address and telephone number; (d) insurance policy number; and (e) date of birth for natural persons; 2. If it is an organisation, the UA operator should include the	EASA	Mar-19	Open category and Specific	Opinion published											
	Marking and Registration							ASTM F2851-10 Standard Practice for UAS Registration and Marking (Excluding Small Unmanned Aircraft Systems)	This practice follows ICAO Annex 7 SARPS except in areas where the unique aspects of UAS may not allow compliance. In these cases, this document will address the issue and recommend the need for an alternate compliance method.	ASTM F38 Unmanned Aircraft Systems		standard	published					
	Geo-awareness	Opinion No.1 2018	Appendix 2,3,4 to delegated act — Geoawareness system A UAS Class C1, C2 and C3 shall: The UAS shall be equipped with a geo-awareness system providing: (a) an interface to load and update data containing information on airspace limitations, as defined by Regulation (EU) .../... [R], which ensures that the process of loading or updating of such data does not degrade its integrity and validity; (b) a warning alert when a potential breach of airspace limitations is detected; and (c) information on its status as well as a warning alert when the positioning or navigation of the UA cannot ensure the proper functioning of the system;	EASA	Mar-19	Open category and Specific	Opinion published											
	Definition of zones	Opinion No.1 2018	Article 11 Airspace conditions for UAS operations 1. Member States may establish airspace restrictions on zones in which one or more of the following conditions applies: (a) certain UAS operations are not permitted without prior authorisation or are not permitted at all; (b) access is only allowed for certain UAS classes; (c) access is only allowed for UAS equipped with electronic identification and/or geo-awareness systems; (d) UAS operations comply with the specified environmental standards. 2. Member States may define airspace in which UAS operations are exempted from one or more of the 'open' category requirements of this Regulation, and in which operators are not required to hold an authorisation or submit a declaration. 3. Member States shall publish the information on airspace established in accordance with paragraphs 1 or 2 of this Article, as well as on how, if required, authorisation may be obtained, in a manner and format established by EASA.	EASA	Jan-18	Open category and Specific	Opinion published											
	U-space							MASPS for UAS Geo-Fencing	"Minimum Aviation Systems Performance Standard for UAS geo-fencing" defining minimum system level end-to-end requirements for the implementation of the geo-fencing function for UAS.	EUROCAE WG-105	Nov-18	standard	ongoing					
	U-space							MOPS for UAS Geo-Fencing	"Minimum Operational Performance Standard for UAS geo-fencing" defining minimum requirements for the geo-fencing function at the level of individual components.	EUROCAE WG-105	Jun-19	standard	planned					
3	Command, Control and Communication																	
M	C3 datalink and communication							MOPS (Terrestrial LOS)	Minimum Operational Performance Standard for the terrestrial Line of Sight Command and Control Data Link	EUROCAE WG-105	Jun-20	standard	ongoing					
M	C3 datalink and communication							MOPS (SATCOM)	Minimum Operational Performance Standard for the satellite Command and Control Data Link	EUROCAE WG-105	Nov-18	standard	ongoing					
M	C3 datalink and communication							MASPS	Minimum Aviation System Performance Standard for the Command and Control Link	EUROCAE WG-105	Sep-19	standard	ongoing					
	C3 datalink and communication							ASTM F3002-14a Standard Specification for Design of the Command and Control System for Small Unmanned Aircraft Systems (sUAS)	This specification is provided as a consensus standard in support of an application to a nation's governing aviation authority (GAA) for a permit to operate a small unmanned aircraft system (sUAS) for commercial or public use purposes. This standard outlines the general, spectrum and link requirements for C2.	ASTM F38 Unmanned Aircraft Systems		standard	published				FAA Notice Of Availability (NOA) Pending approval of ASTM WK57659 as foundational document	
	C3 datalink and communication							AIR6514 UxS Control Segment (UCS) Architecture: Interface Control Document (ICD)	This interface control document (ICD) specifies all software services in the Unmanned Systems (UxS) Control Segment Architecture, including interfaces, messages, and data model.	SAE AS-4UCS Unmanned Systems (UxS) Control Segment Architecture		information report	published					
M	C3 datalink and communication							AIR6514A UxS Control Segment (UCS) Architecture: Interface Control Document (ICD)	This interface control document (ICD) specifies all software services in the Unmanned Systems (UxS) Control Segment Architecture, including interfaces, messages, and data model.	SAE AS-4UCS Unmanned Systems (UxS) Control Segment Architecture	Nov-18	information report	ongoing					
M	C3 datalink and communication							AS6522A Unmanned Systems (UxS) Control Segment (UCS) Architecture: Technical Governance	The UCS technical governance comprises a set of policies, processes, and standard definitions to establish consistency and quality in the development of architecture artifacts and documents. It provides guidance for the use of adopted industry standards and modeling conventions in the use of Unified Modeling Language (UML) and Service Oriented Architecture Modeling Language (SoAML), including where the UCS Architecture deviates from normal UML conventions. This document identifies the defining policies, guidelines, and standards of technical governance in the following subjects:	SAE AS-4UCS Unmanned Systems (UxS) Control Segment Architecture	Nov-18		ongoing					

	C3 datalink and communication								AIR6515 Unmanned Systems (UxS) Control Segment (UCS) Architecture: EA Version of UCS ICD Model	This User Guide describes the content of the Enterprise Architect (EA) version of the UCS Architectural Model and how to use this model within the EA modeling tool environment. The purpose of the EA version of the UCS Architectural Interface Control Document (ICD) model is to provide a working model for Enterprise Architect tool users and to serve as the source model for the Rational Software Architect (RSA) and Rhapsody models (AIR6516 and AIR6517). The AIR6515 EA Model has been validated to contain the same content as the AS6518 model for - all UCS ICD interfaces - all UCS ICD messages - all UCS ICD data directly or indirectly referenced by ICD messages and interfaces - the Domain Participant, Information, Service, and Non Functional Properties Models. Prerequisites for using the AIR6515 EA Model include -access to / experience with Enterprise Architect 10 or higher, Corporate Edition. -experience with the Unified Modeling Language (UML) -an understanding of the UCS Architectural Model as originally created in the EA Model AS6518-MODEL	SAE AS-4UCS Unmanned Systems (UxS) Control Segment Architecture		information report	published	
	C3 datalink and communication								AIR6516 Unmanned Systems (UxS) Control Segment (UCS) Architecture: RSA Version of UCS ICD Model	This User Guide describes the content of the Rational Software Architect (RSA) version of the UCS Architectural Model and how to use this model within the RSA modeling tool environment. The purpose of the RSA version of the UCS Architectural Interface ICD model is to provide a model for Rational Software Architect (RSA) users, derived from the Enterprise Architect (EA) ICD model (AIR6515). The AIR6516 EA Model, and by derivation, the AIR6516 RSA Model, have been validated to contain the same content as the AS6518 model for - all UCS ICD interfaces - all UCS ICD messages - all UCS ICD data directly or indirectly referenced by ICD messages and interfaces - the Domain Participant, Information, Service and Non Functional Properties Models. Prerequisites for using the AIR6516 RSA Model include -access to Rational Software Architect, Version 9.0 or higher. This release was checked with version 9.1.1. -experience with the Unified Modeling Language (UML) -an understanding of the UCS Architectural Model as originally created in the EA model AS6518-MODEL	SAE AS-4UCS Unmanned Systems (UxS) Control Segment Architecture		Information Report	published	
	C3 datalink and communication								AIR6517 Unmanned Systems (UxS) Control Segment (UCS) Architecture: Rhapsody Version of UCS ICD Model	This User Guide describes the content of the Rhapsody version of the UCS Architectural Model and how to use this model within the Rhapsody modeling tool environment. The purpose of the Rhapsody version of the UCS Architectural Interface Control Document (ICD) model is to provide a model for Rhapsody users, derived from the Enterprise Architect (EA) model (AIR6515). The AIR6515 EA Model, and by derivation, the AIR6517 Rhapsody Model, have been validated to contain the same content as the AS6518 model for - all UCS ICD interfaces - all UCS ICD messages - all UCS ICD data directly or indirectly referenced by ICD messages and interfaces - the Domain Participant, Information, Service and Non Functional Properties Models. Prerequisites for using the AIR6517 Rhapsody Model include -access to / experience with the Rhapsody Modeling Tool Environment version 8.1 or higher. This product was validated using Rational Rhapsody Architect for System Engineers, version 8.1.1. -experience with the Unified Modeling Language (UML) -an understanding of the UCS Architectural Model as originally created in the EA model AS6518-MODEL	SAE AS-4UCS Unmanned Systems (UxS) Control Segment Architecture		information report	published	
	C3 datalink and communication								AIR6519 UxS Control Segment (UCS) Architecture: UCTRACE	The Use Case Trace (UCTRACE) is SAE publication AIR6519 of the Department of Defense Unmanned Control Segment (UCS) Architecture. This document is the SAE publication of the Department of Defense UAS Control Segment (UCS) Architecture: Use Case Trace (UCTRACE) Version 3.4(PR) approved for Distribution A public release 15.S-1859. This information is produced from a script run against the System Use Case Model contained in the UCS Architecture Model AS6518-MODEL.asp configuration item. The System Use Case Model includes, at its lowest level of elaboration, use cases Level 2/3 (L2/L3) that describe specific scenarios of message exchanges between Actors and internal system Participants via ServiceInterfaces. These message exchanges provide a way to create detailed traces that answer the question: "What UCS service interfaces must my components implement to satisfy functional requirements represented by a given Level 2/3 UCS use case?" The AIR6519-UCTRACE spreadsheet contains trace information derived directly from the message sequences in the L2/L3 use cases.	20-Dec-16		information report	published	
	C3 datalink and communication								AIR6520 Unmanned Systems (UxS) Control Segment (UCS) Architecture: Version Description Document	Governance of the Unmanned Aircraft System (UAS) Control Segment (UCS) Architecture was transferred from the United States Office of the Secretary of Defense (OSD) to SAE International in April 2015. Consequently, a subset of the UCS Architecture Library Release 3.4(PR) has been published under SAE as the Unmanned Systems (UxS) Control Segment (UCS) Architecture. AS6512. This Version Description Document (VDD) describes the correspondence and differences between the two architecture libraries.	SAE AS-4UCS Unmanned Systems (UxS) Control Segment Architecture		Information Report	published	
	C3 datalink and communication								AIR6521 Unmanned Systems (UxS) Control Segment (UCS) Architecture: Data Distribution Service (DDS)	This platform specific Interface Control Document (ICD) provides an example mapping to the Object Management Group's (OMG) Data Distribution Service (DDS) infrastructure middleware. The mapping is based on the Unmanned Systems (UxS) Control Segment (UCS) Architecture: Model, AS6518. A series of non-normative implementation choices have been made that are specific to this ICD. These implementation choices may not be appropriate for different system implementations. The machine readable ICD and result of this mapping and implementation choices are provided with AIR6521. Use and understanding of this document assumes a working knowledge of the UCS Architecture, the model structure and its contents.	SAE AS-4UCS Unmanned Systems (UxS) Control Segment Architecture		information report	published	
	C3 datalink and communication								AS6512 Unmanned Systems (UxS) Control Segment (UCS) Architecture: Architecture Description	This document is the Architecture Description (AD) for the SAE Unmanned Systems (UxS) Control Segment (UCS) Architecture. This AD serves as the official designation of the UCS Architecture - SAE AS6512. The UCS Architecture is expressed by a library of SAE publications as referenced herein. The other publications in the UCS Architecture Library are AS6513, AIR6514, AIR6515, AIR6516, AIR6517, AS6518, AIR6519, AIR6520, AIR6521, and AS6522.	SAE AS-4UCS Unmanned Systems (UxS) Control Segment Architecture		standard	published	
	C3 datalink and communication								AS6513 Unmanned Systems (UxS) Control Segment (UCS) Architecture: Conformance Specification	This document is the authoritative specification within the SAE Unmanned Systems (UxS) Control Segment (UCS) Architecture for establishing conformance requirements for UCS products. The UCS products addressed by this specification are UCS software components and UCS software configurations that provide one or more UCS services, and UCS systems that employ one or more UCS services. The conformance of UCS products is determined by assessing the conformance of the UCS product description artifacts to the UCS Architecture. The UCS product description includes test artifacts.	SAE AS-4UCS Unmanned Systems (UxS) Control Segment Architecture		standard	published	
	C3 datalink and communication								AS6518 Unmanned Systems (UxS) Control Segment (UCS) Architecture: UCS Architecture Model	This brief User Guide recaps the content of the AS6518 UCS Architectural Model described in detail in AS6512 UCS Architecture: Architecture Description. The purpose of the UCS Architecture Model is to provide the authoritative source for other models and products within the UCS Architecture as shown in the AS6512 UCS Architecture: Architecture Description. Prerequisites for using the AS6518 EA Model include -access to / experience with Enterprise Architect 10 or higher, Corporate Edition. - experience with the Unified Modeling Language (UML) -installation of the [included] UCS_MDG.xml add in for Sparx Enterprise Architect per instructions below	SAE AS-4UCS Unmanned Systems (UxS) Control Segment Architecture		standard	published	

									AS4522 Unmanned Systems (UxS) Control Segment (UCS) Architecture Technical Governance	The UCS technical governance comprises a set of policies, processes, and standard definitions to establish consistency and quality in the development of architecture artifacts and documents. It provides guidance for the use of adopted industry standards and modeling conventions in the use of Unified Modeling Language (UML) and Service Oriented Architecture Modeling Language (SoAML), including where the UCS Architecture deviates from normal UML conventions. This document identifies the defining policies, guidelines, and standards of technical governance in the following subjects: industry standards adopted by the AS-4UCS Technical Committee. These are the industry standards and specifications adopted by AS-4UCS in the generation and documentation of the architecture. - UCS Architecture Development: UCS specific policies on the development of the UCS Architecture. The AS-4UCS Technical Committee governance policies are intentionally minimal. The object is to provide direction specific to the intent and scope of developing architecture artifacts that follow a consistent set of specifications and industry best practices. Standards are referenced within policies. Standards may place constraints on policies that are implemented by processes. Each process is intended to guide the development of architecture artifacts. For example, a standard may dictate that a UML diagram be modeled in a particular methodology using only approved stereotypes from the SoAML UML profile. UCS technical governance applies to the following technical work products that are generated within the AS-4UCS Technical Committee. It is not applicable to third party developers, programs, or any other consumer of the UCS Architecture.	SAE AS-4UCS Unmanned Systems (UxS) Control Segment Architecture			standard	published	
	Navigation								WKS8931 Evaluating AerialResponse RobotManeuvering: Maintain Position and Orientation	A suite of standard test methods has been developed to measure maneuverability, endurance,communications, durability, logistics,autonomy, and safety to guide purchasing decisions,support operator training and measure proficiency.	ASTM E54 Homeland Security Applications	Apr-18	standard	ongoing	Publication Delayed -Full Committee Meeting Feb 28- Mar 2 2018 for adjudication of comments	
	Navigation								WKS8932 Evaluating AerialResponse RobotManeuvering: Orbit a Point	A suite of standard test methods has been developed to measure maneuverability, endurance,communications, durability, logistics,autonomy, and safety to guide purchasing decisions,support operator training and measure proficiency.	ASTM E54 Homeland Security Applications	Apr-18	standard	ongoing	Publication Delayed -Full Committee Meeting Feb 28- Mar 2 2018 for adjudication of comments	
	Navigation								WKS8933 Evaluating AerialResponse RobotManeuvering: Avoid Static Obstacles	A suite of standard test methods has been developed to measure maneuverability, endurance,communications, durability, logistics,autonomy, and safety to guide purchasing decisions,support operator training and measure proficiency.	ASTM E54 Homeland Security Applications	Jun-18	standard	ongoing		
	Navigation								WKS8934 Evaluating AerialResponse RobotManeuvering: Pass Through Openings	A suite of standard test methods has been developed to measure maneuverability, endurance,communications, durability, logistics,autonomy, and safety to guide purchasing decisions,support operator training and measure proficiency.	ASTM E54 Homeland Security Applications	Apr-18	standard	ongoing	Publication Delayed -Full Committee Meeting Feb 28- Mar 2 2018 for adjudication of comments	
	Navigation								WKS8935 Evaluating AerialResponse RobotManeuvering: Land Accurately (Vertical)	A suite of standards test methods has been developed to measure maneuverability, endurance,communications, durability, logistics,autonomy, and safety to guide purchasing decisions,support operator training and measure proficiency.	ASTM E54 Homeland Security Applications	Apr-18	standard	ongoing	Publication Delayed -Full Committee Meeting Feb 28- Mar 2 2018 for adjudication of comments	
	C3 datalink and communication								WKS8942 Evaluating AerialResponse RobotRadio Communication Range: Line of Sight	A suite of standards test methods has been developed to measure maneuverability, endurance,communications, durability, logistics,autonomy, and safety to guide purchasing decisions,support operator training and measure proficiency.	ASTM E54 Homeland Security Applications	Apr-18	standard	ongoing	Publication Delayed -Full Committee Meeting Feb 28- Mar 2 2018 for adjudication of comments	
	C3 datalink and communication								WKS8941 Evaluating AerialResponse RobotRadio Communications Range: Non Line of Sight	A suite of standards test methods has been developed to measure maneuverability, endurance,communications, durability, logistics,autonomy, and safety to guide purchasing decisions,support operator training and measure proficiency.	ASTM E54 Homeland Security Applications	Apr-18	standard	ongoing	Publication Delayed -Full Committee Meeting Feb 28- Mar 2 2018 for adjudication of comments	
	C3 datalink and communication								STANAG 4660 - Interoperable Command and Control Datalink for Unmanned Systems	Common standard Line-Of-Sight command and control data link for the safe and reliable operation of unmanned systems within a joint, coalition and controlled airspace operating environment.	NATO NNAGUJGUAS		standard	published		
	Navigation								SAE6856 Improving Navigation Solutions Using Raw Measurements from Global Navigation Satellite System (GNSS) Receivers	This recommended practice provides users with the technical requirements and methods for accessing, viewing, and processing raw GNSS receiver measurements for improved unmanned vehicle navigation solutions.	SMCPNT Position, Navigation, and Timing Committee	Mar-19	standard	ongoing		
	Navigation								SAE6857 Requirements for a Terrestrial Based Position, Navigation, and Timing (PNT) System to Improve Navigation Solutions and Ensure Critical Infrastructure Security	This recommended practice defines the technical requirements for a terrestrial-based PNT system to improve vehicle (e.g. unmanned, aerial, ground, maritime) positioning/navigation solutions and ensure critical infrastructure security, complementing GNSS technologies.	SMCPNT Position, Navigation, and Timing Committee	Mar-19	standard	ongoing		
	C3 datalink and communication								MASPS on C3 Spectrum Management for the 5030/5091 MHz band	Minimum Aviation Systems Performance Standard defining requirements for the management of the 5030/5091 MHz band fr use by C2 Link Services	EUROCAE WG-105	Dec-18	standard	planned		
M	C3 datalink and communication								Guidance on Spectrum Access, Use and Management	Guidance material describing considerations for the use of spectrum for UAS purposes	EUROCAE WG-105	Mar-19	guidance	ongoing		
	Cyber security	Opinion No.1 /2018	Appendix 3, 4 to Delegated Act A UAS Class C2 and C3 shall be equipped with a remote pilot data link protected against unauthorised access to the command and control functions;	EASA	Mar-19	open	Opinion published									
	Cyber security								MASPS on RPAS C3 Security	Minimum Aviation Systems Performance Standard defining system level requirements for the application of Security measures to the UAS C3 Link	EUROCAE WG-105	Jun-19	standard	ongoing		
M	C3 datalink and communication								Guidance on RPAS C3 security	Guidance material for the application of the MASPS listed above	EUROCAE WG-105	Dec-19	guidance	ongoing		
	C3 datalink and communication	EASA Decision	OSD#6 C3 link performance is appropriate for the operation	EASA	May-19	Specific	ongoing									
	C3 datalink and communication	EASA Decision	OSD#16 Multi crew coordination. (Criterion #3 Communication devices)	EASA	May-19	Specific	ongoing									
4 Detect and Avoid																
M	Detect and avoid								MASPS	Minimum Aviation System Performance Standard (End-to-end Requirements at system level) for DAA of IFR Flights in class A-C airspace.	EUROCAE WG-105	Dec-18	standard	ongoing		
M	Detect and avoid								MOPS	Minimum Operational Performance Standard (Requirements at equipment level) for DAA of IFR Flights in class A-C airspace.	EUROCAE WG-105	Dec-19	standard	ongoing		
M	Detect and avoid								OSED	Operational Services and Environment Description for DAA for DAA in Class D-G airspaces under VFR/IFR	EUROCAE WG-105	Aug-18	standard	ongoing		
M	Detect and avoid								MASPS	Minimum Aviation System Performance Standard (End-to-end Requirements at system level) for DAA against conflicting traffic for RPAS operating under IFR and VFR in all airspace classes	EUROCAE WG-105	Dec-19	standard	ongoing		

	Detect and avoid									MOPS	Minimum Operational Performance Standard (Requirements at equipment level) for DAA against conflicting traffic for RPAS operating under IFR and VFR in all airspace classes	EUROCAE WG-105	Jun-20	standard	planned	
M	Detect and avoid									OSED	Operational Services and Environment Description for DAA in Very Low Level Operations	EUROCAE WG-105	Jun-19	standard	planned	
M	Detect and avoid									MOPS	Minimum Operational Performance Standard (Requirements at equipment level) for DAA at Very Low Level (VLL)	EUROCAE WG-105	Jun-20	standard	planned	
M	Detect and avoid									STANREC 4811 Ed. 1) AEP- 101 Ed. A Ver. 1 "UAS sense and avoid"	To detail comprehensive guidance and recommended practice for the development of Sense and Avoid systems, referencing and providing guidance regarding application of existing standards and best practice.	NATO FINAS	Feb-18	guide	published	
D	Detect and avoid									WK6268	Defines minimum performance standards Comprehensive DAA Standard under annex to define test methods AND minimum performance standards for DAA systems and sensors applicable to smaller UAS BLVLOS operations for the protection of manned aircraft in lower altitude airspace	ASTM F38 Unmanned Aircraft Systems	Jun-19	standard	ongoing	The work it is now being covered under WK 6268/6269
	Detect and avoid									WK6269 Test Method for DAA	Covering systems and sensors Comprehensive DAA Standard under annex to define test methods AND minimum performance standards for DAA systems and sensors applicable to smaller UAS BLVLOS operations for the protection of manned aircraft in lower altitude airspace	ASTM F38 Unmanned Aircraft Systems	Jun-19	standard	ongoing	Working Group formed under terms of reference. Number changed to WK6269 instead of WK6268
D	Detect and avoid									WK6268	Defines minimum performance standards Comprehensive DAA Standard under annex to define test methods AND minimum performance standards for DAA systems and sensors applicable to smaller UAS BLVLOS operations for the protection of manned aircraft in lower altitude airspace	ASTM F38 Unmanned Aircraft Systems	Jun-19	standard	ongoing	Performance requirements to be covered under WK6268
5 RPAS Automation																
	Development assurance (Software)									ASTM F3269 Standard Practice for Methods to Safely Bound Flight Behavior of Unmanned Aircraft Systems Containing Complex Functions	This standard practice defines design and test best practices that if followed would provide guidance to an applicant for providing evidence to the civil aviation authority (CAA) that the flight behavior of an unmanned aircraft system (UAS) containing complex function(s) is constrained through a run-time assurance (RTA) architecture to maintain an acceptable level of flight safety.	ASTM F38 Unmanned Aircraft Systems		standard	published	FAA Notice Of Availability (NOA) Pending approval of ASTM WK57659 as foundational document
A	Automatic modes, takeoff, Landing, taxiing									ASTM WK65056 Revision to ASTM F3269 Standard Practice for Methods to Safely Bound Flight Behavior of Unmanned Aircraft Systems Containing Complex Functions	Goal is to develop the standard to a level of capability that defines run-time monitoring (RTA) attributes to a level that the FAA or CAA will agree that monitors developed to this standard are sufficient to allow the UAS to evolve the complex function with its associated avionics equipment and sensors without requiring vehicle recertification as the CONOPS evolve after initial certification. a. Provide additional guidance on Safety Monitor design best practices, to explicitly include guidance on partitioning, dissimilarity, and the option for multiple individual safety monitors comprising the Safety Monitor function, as well as defining safety monitor classes and key attributes. b. Provide additional use cases as Appendices. c. Provide additional information contrasting the F3269 approach with other architectural approaches (e.g., SAE ARP 4754A, RTCA DO-178C). d. Modify requirements to performance based to allow multiple implementation and implementation architectures e. Make additional updates as required.	ASTM F38 Unmanned Aircraft Systems	September 2019	standard		TOR being developed
M	Automatic modes, takeoff, Landing, taxiing									ED-252 OSED	Operational Services and Environment Description for Automatic Take-Off and Landing	EUROCAE WG-105		standard	published	
	Automatic modes, takeoff, Landing, taxiing									MASPS	Minimum Aviation System Performance Standard (End-to-end Requirements at system level) for Automatic Take-Off and Landing	EUROCAE WG-105	Jun-20	standard	planned	
M	Automatic modes, takeoff, Landing, taxiing									ED-251 OSED	Operational Services and Environment Description for Automatic Taxiing	EUROCAE WG-105		standard	published	
	Automatic modes, takeoff, Landing, taxiing									MASPS	Minimum Aviation System Performance Standard (End-to-end Requirements at system level) for Automatic Taxiing	EUROCAE WG-105	Jun-20	standard	planned	
	Emergency recovery/terminations systems	Opinion No.1 2018	Appendix 3 and 4 to delegated act A UAS Class C2 and C3 shall: in case of loss of data link, have a reliable and predictable method	EASA	Mar-19	open category and specific	Opinion published									
M	Emergency recovery/terminations systems									OSED	Operational Services and Environment Description for Automation and Emergency Recovery	EUROCAE WG-105	Dec-18	standard	ongoing	
	Emergency recovery/terminations systems									MASPS	Minimum Aviation System Performance Standard (End-to-end Requirements at system level) for automation and Emergency Recovery	EUROCAE WG-105	Jun-20	standard	planned	
6 Design & Airworthiness																
	UA Design and Airworthiness	Opinion No.1 2018	Appendix 1, 2, 3, 4, 5 to delegated act A UAS Class C0, C1, C2, C3 and C4 shall: be designed and manufactured to fly safely;	EASA	Mar-19	open	Opinion published									
M	Development assurance (Software)									ASTM F3151 Standard Specification for Verification of Avionics Systems1	This specification provides a process by which the intended function and compliance with safety objectives of avionics systems may be verified by system-level testing. Software and hardware development assurance are not in the scope of this specification and this specification should not be used if a development assurance process is required.	ASTM F39 Aircraft Systems		standard	published	This will be reference in AC for Special Class §21.17(b) To be uses where appropriate in lieu of DO 178. NEW DELIVERABLE
	UA Design and Airworthiness									AS6009A JAUS Mobility Service Set	This document defines a set of standard application layer interfaces called JAUS Mobility Services. JAUS Services provide the means for software entities in an unmanned system or system of unmanned systems to communicate and coordinate their activities. The Mobility Services represent the vehicle platform-independent capabilities commonly found across all domains and types of unmanned systems (referred to as UAVs). At present, over 15 services are defined in this document many of which were updated in this revision to support Unmanned Underwater Vehicles (UUVs).	SAE AS-4/JAUS Joint Architecture for Unmanned Systems Committee		standard	published	
	UA Design and Airworthiness									AS6684B JAUS Service Interface Definition Language	The SAE Aerospace Information Report AIR5315 - Generic Open Architecture (GOA) defines "a framework to identify interface classes for applying open systems to the design of a specific hardware/software system." [see] JAUS Service (Interface) Definition Language defines an XML schema for the interface definition of services at the Class 4L, or Application Layer, and Class 3L, or System Services Layer, of the Generic Open Architecture stack (see Figure 1). The specification of JAUS services shall be defined according to the JAUS Service (Interface) Definition Language document.	SAE AS-4/JAUS Joint Architecture for Unmanned Systems Committee		standard	published	
	UA Design and Airworthiness									AS6062 JAUS Mission Spooling Service Set	This document defines a set of standard application layer interfaces called JAUS Mission Spooling Services. JAUS Services provide the means for software entities in an unmanned system or system of unmanned systems to communicate and coordinate their activities. The Mission Spooling Services represent the platform-independent capabilities commonly found across all domains and types of unmanned systems. At present, 1 service is defined in this document (more services are planned for future versions of this document) - Mission Spooler. Stores mission plans, coordinates mission plans, and parcels out elements of the mission plan for execution The Mission Spooler service is described by a JAUS Service Definition (JSD) which specifies the message set and protocol required for compliance. The JSD is fully compliant with the JAUS Service Interface Definition Language (JSIDL).	SAE AS-4/JAUS Joint Architecture for Unmanned Systems Committee		standard	published	

	UA Design and Airworthiness							AS6060 JAUS Environment Sensing Service Set	This document defines a set of standard application layer interfaces called JAUS Environment Sensing Services. JAUS Services provide the means for software entities in an unmanned system or system of unmanned systems to communicate and coordinate their activities. The Environment Sensing Services represent typical environment sensing capabilities commonly found across all domains and types of unmanned systems in a platform-independent manner. At present, five services are defined in this document: • Range Sensor: Determine the proximity of objects in the platform's environment • Visual Sensor: Provides common configuration and setup for different types of imaging systems • Digital Video: A type of Visual Sensor that manages digital video • Analog Video: A type of Visual Sensor that manages analog video • Still Image: A type of Visual Sensor that manages and encodes individual digital images Each service is described by a JAUS Service Definition (JSD) which specifies the message set and protocol required for compliance. Each JSD is fully compliant with the JAUS Service Interface Definition Language [AS5684].	SAE AS-4JAUS Joint Architecture for Unmanned Systems Committee		standard	published	
	HMI							AS6040 JAUS HMI Service Set	This document defines a set of standard application layer interfaces called JAUS HMI Services. JAUS Services provide the means for software entities in an unmanned system or system of unmanned systems to communicate and coordinate their activities. The HMI Services represent the platform-independent Human Machine Interface (HMI) capabilities commonly found across all domains and types of unmanned systems. Five services are defined in this document: • Drawing • Plotting Device • Keyboard • Digital Control • Analog Control Each service is described by a JAUS Service Definition (JSD) which specifies the message set and protocol required for compliance. Each JSD is fully compliant with the JAUS Service Interface Definition Language (JSIDL) [AS5684].	SAE AS-4JAUS Joint Architecture for Unmanned Systems Committee		standard	published	
	UA Design and Airworthiness							AS5710A JAUS Core Service Set	This document defines a set of standard application layer interfaces called JAUS Core Services. JAUS Services provide the means for software entities in an unmanned system or system of unmanned systems to communicate and coordinate their activities. The Core Services represent the infrastructure commonly found across all domains and types of unmanned systems. At present, eight services are defined in this document: • Transport Service: Abstracts the functionality of the underlying communication transport layer • Events Service: Establishes a publish/subscribe mechanism for automatic messaging • Access Control: Manages preemptable exclusive control for safety critical operations • Management: Defines component life-cycle management • Time: Allows clients to query and set the system time for the component • Liveness: Provides a means to maintain connection liveness between communicating components • Discovery: Governs automatic discovery of remote entities and their capabilities • List Manager: Encompasses behavior common to doubly linked lists Each service is described by a JAUS Service Definition (JSD) which specifies the message set and protocol required for compliance. Each JSD is fully compliant with the JAUS Service Interface Definition Language (JSIDL).	SAE AS-4JAUS Joint Architecture for Unmanned Systems Committee		standard	published	
	UA Design and Airworthiness							ARRP012A JAUS Compliance and Interoperability Policy	This document, the JAUS Compliance and Interoperability Policy (ARRP012), recommends an approach to documenting the complete interface of an unmanned system or component in regard to the application of the standard set. While non-SAE AS-4 JAUS documents are referenced in this ARP they are not within the scope of this document and should be viewed as examples only.	SAE AS-4JAUS Joint Architecture for Unmanned Systems Committee		recommended practice	published	
	UA Design and Airworthiness							AIR5645A JAUS Transport Considerations	This SAE Aerospace Information Report (AIR) discusses characteristics of data communications for the Joint Architecture for Unmanned Systems (JAUS). This document provides guidance on the aspects of transport media, unmanned systems and the characteristics of JAUS itself that are relevant to the definition of a JAUS transport specification.	SAE AS-4JAUS Joint Architecture for Unmanned Systems Committee		information report	published	
	UA Design and Airworthiness							AS5669A JAUS/SDP Transport Specification	This SAE Aerospace Standard (AS) specifies a data communications layer for the transport of messages defined by the Joint Architecture for Unmanned Systems (JAUS) or other Software Defined Protocols (SDP). This Transport Specification defines the formats and protocols used for communication between compliant entities for all supported link-layer protocols and media. Although JAUS is the SDP used as the example implemented throughout this document, AS5669 can be used for any SDP that meets the required capabilities. A Software Defined Protocol is defined as an application data interface for communicating between software elements. The SDP is agnostic of the underlying communications protocol and in fact communicates in much the same manner regardless if the communicating entities are collocated in the same memory space or separated by a satellite link.	SAE AS-4JAUS Joint Architecture for Unmanned Systems Committee		standard	published	
	UA Design and Airworthiness							AS6091 JAUS Unmanned Ground Vehicle Service Set	This document defines a set of standard application layer interfaces called JAUS Unmanned Ground Vehicle Services. JAUS Services provide the means for software entities in an unmanned system or system of unmanned systems to communicate and coordinate their activities. The Unmanned Ground Vehicle Services represent the platform-specific capabilities commonly found in UGVs, and augment the Mobility Service Set [AS6009] which is platform-agnostic. At present ten (10) services are defined in this document.	SAE AS-4JAUS Joint Architecture for Unmanned Systems Committee		standard	published	
	UA Design and Airworthiness							AS6057A JAUS Manipulator Service Set	This document defines a set of standard application layer interfaces called JAUS Manipulator Services. JAUS Services provide the means for software entities in an unmanned system or system of unmanned systems to communicate and coordinate their activities. The Manipulator Services represent platform-independent capabilities commonly found across domains and types of unmanned systems. At present, twenty-five (25) services are defined in this document.	SAE AS-4JAUS Joint Architecture for Unmanned Systems Committee		standard	published	
	UA Design and Airworthiness							ARRP227 JAUS Messaging over the OMG Data Distribution Service (DDS)	This document defines a standard representation of JAUS AS5684A message data in DDS IDL defined by the Object Management Group (OMG) CORBA 3.2 specification. This document does NOT address how JAUS transport considerations or JAUS service protocols are implemented on OMG DDS platforms.	SAE AS-4JAUS Joint Architecture for Unmanned Systems Committee		recommended practice	published	
	UA Design and Airworthiness							AIR5665B Architecture Framework for Unmanned Systems	This SAE Aerospace Information Report (AIR) describes the Architecture Framework for Unmanned Systems (AFUS). AFUS comprises a Conceptual View, a Capabilities View, and an Interoperability View. The Conceptual View provides definitions and background for key terms and concepts used in the unmanned systems domain. The Capabilities View uses terms and concepts from the Conceptual View to describe capabilities of unmanned systems and of other entities in the unmanned systems domain. The Interoperability View provides guidance on how to design and develop systems in a way that supports interoperability.	SAE AS-4JAUS Joint Architecture for Unmanned Systems Committee		information report	published	
	UA Design and Airworthiness							AIR5664A JAUS History and Domain Model	The purpose of this SAE Aerospace Information Report (AIR) is two-fold: to inform the reader of the extent of effort that went into the development of the Joint Architecture for Unmanned Systems (JAUS), and to capture for posterity the domain analysis that provides the underpinnings for the work by the AS-4 Committee (Unmanned Systems).	SAE AS-4JAUS Joint Architecture for Unmanned Systems Committee		information report	published	
M	UA Design and Airworthiness							AS6062A JAUS Mission Spooling Service Set	This document defines a set of standard application layer interfaces called JAUS Mission Spooling Services. JAUS Services provide the means for software entities in an unmanned system or system of unmanned systems to communicate and coordinate their activities. The Mission Spooling Services represent the platform-independent capabilities commonly found across all domains and types of unmanned systems. At present, 1 service is defined in this document (more services are planned for future versions of this document): • Mission Spooler: Stores mission plans, coordinates mission plans, and parcels out elements of the mission plan for execution The Mission Spooler service is described by a JAUS Service Definition (JSD) which specifies the message set and protocol required for compliance. The JSD is fully compliant with the JAUS Service Interface Definition Language (JSIDL).	SAE AS-4JAUS Joint Architecture for Unmanned Systems Committee		standard	published	
	UA Design and Airworthiness							AS6111 JAUS Unmanned Maritime Vehicle Service Set	This document defines a message-passing interface for services representing the platform-specific capabilities common across unmanned maritime vehicles.	SAE AS-4JAUS Joint Architecture for Unmanned Systems Committee	Jun-19	standard	ongoing	

	UA Design and Airworthiness							AS6971 Test Protocol for UAS Reciprocating (Intermittent) Engines as Primary Thrust Mechanism	This standard is intended to provide a method (or methods) to obtain repeatable and consistent measurements to reflect true engine performance and durability in customer. Standardized methodology is needed to normalize engine performance to fairly rate engine operating variables and parameters. Operational protocols will be defined according to engine class and will be based on those developed for on-highway applications. Based on typical engine operation, a series of speed and load combinations and/or sequences will be determined. The scope will include dynamometer based testing and static propeller-based experiments. The industry consists of many platforms that use reciprocating engines as the main (or sole) provider of rotational energy to propeller. There also exists a significant move towards hybrid-based engine-battery systems that are expected to have different operational requirements. This standard will focus on those using the engine as the main thrust provider, but allowances will also be considered for hybrid designs. The scope will include power correction methodologies to provide a more accurate description of performance.	SAE E-39 Unmanned Aircraft Propulsion Committee	May-19	standard	ongoing	
	UA Design and Airworthiness							AS6984 Ground support equipment (preheaters, starters, fuel pumps, fuel couplings, fuel mixing, fuel filters, preflight weight/balance, bore-weighing of payload, storage containers, alignment hardware, wheel chocks, "remove before flight" items, electronic and software links.	A review of icing materials that would be educational to a designer of a UAV ion protection system is provided. Additionally, the differences between unmanned and manned ice protection systems are explored along with a discussion on how these differences can be addressed.	SAE E-39 Unmanned Aircraft Propulsion Committee	Jun-19	standard	planned	
	UA Design and Airworthiness							AS6988 Propeller hubs		SAE E-39 Unmanned Aircraft Propulsion Committee	Jul-19	standard	planned	
	UA Design and Airworthiness							ARP6989 Propeller Information Report		SAE E-39 Unmanned Aircraft Propulsion Committee	Aug-19	information report	ongoing	
M	UA Design and Airworthiness							AIR6962 Ice Protection for Unmanned Aerial Vehicles		SAE AC-9C Aircraft Icing Technology Committee	Dec-18	information report	ongoing	
	UA Design and Airworthiness							ARP9410 Aerospace Vehicle Management Systems - Flight Control Design, Installation and Test of Military Unmanned Aircraft. Specification Guide For	This document establishes recommended practices for the specification of general performance, design, test, development, and quality assurance requirements for the flight control related functions of the Vehicle Management Systems (VMS) of military Unmanned Aircraft (UA), the airborne element of Unmanned Aircraft Systems (UAS), as defined by ASTM F 2395-07. The document is written for military unmanned aircraft intended for use primarily in military operational areas. The document also provides a foundation for considerations applicable to safe flight in all classes of airspace.	SAE A-6 Aerospace Actuation, Control and Fluid Power Systems		recommended practice	published	
	UA Design and Airworthiness							ARP724 Aerospace Testing of Electromechanical Actuators: General Guidelines For	This document provides an overview of the tests, and issues related to testing, that are unique to Electromechanical Actuators (EMAs). The tests, and issues documented, are not necessarily all-inclusive. This document discusses both the tests applicable to EMAs and the test methodologies to accomplish the test objectives. EMAs may be used in a wide variety of applications such as utility, secondary flight controls and primary flight controls, in a wide variety of markets including manned and unmanned civil and military aircraft, small missile fin and thrust vector control applications up to high powered utility and flight controls. EMAs may also have either a rotary or a linear output, be servo controlled or use simple open loop point-to-point or other control topologies. As such this document covers a wide range of potential applications, the application of any given test requirement is determined by the application and the user. This document attempts to provide basic guidance on which tests should be considered for various applications. This document also lists tests that are not unique to EMAs, but are still applicable to EMAs. In these instances a discussion of such tests is not contained in this document, and as applicable, the reader may reference the appropriate documents as indicated in the text. While many EMA configurations include digital power drive electronics (PDE), the specific tests required for the electronic hardware, software, or firmware are outside the scope of this document.	A-6 Aerospace Actuation, Control and Fluid Power Systems		recommended practice	published	
	UA Design and Airworthiness							AIR744™ Aerospace Auxiliary Power Sources	This SAE Aerospace Information Report (AIR) is a review of the general characteristics of power sources that may be used to provide secondary, auxiliary, or emergency power for use in aircraft, space vehicles, missiles, remotely piloted vehicles, air cushion vehicles, surface effect ships, or other vehicles in which aerospace technology is used. The information contained herein is intended for use in the selection of the power source most appropriate to the needs of a particular vehicle or system. The information may also be used in the preparation of a power source specification. Considerations for use in making a trade study and an evaluation of the several power sources are included. More detailed information relating to specific power sources is available in other SAE Aerospace Information Reports or in Aerospace Recommended Practices.	A-6 Aerospace Actuation, Control and Fluid Power Systems		information report	published	
	UA Design and Airworthiness							AS50881F Wiring Aerospace Vehicle	This specification covers all aspects in electrical wire interconnection systems (EWS) from the selection through installation of wiring and wiring devices and optical cabling and termination devices used in aerospace vehicles. Aerospace vehicles include manned and unmanned airplanes, helicopters, lighter-than-air vehicles, missiles and external pods.	SAE AE-8A Elec Wiring and Fiber Optic Interconnect Sys Install Committee		standard	published	
	UA Design and Airworthiness							AS50881G Wiring Aerospace Vehicle	This specification covers all aspects in electrical wire interconnection systems (EWS) from the selection through installation of wiring and wiring devices and optical cabling and termination devices used in aerospace vehicles. Aerospace vehicles include manned and unmanned airplanes, helicopters, lighter-than-air vehicles, missiles and external pods.	SAE AE-8A Elec Wiring and Fiber Optic Interconnect Sys Install Committee	Dec-18	standard	ongoing	
	UA Design and Airworthiness							AS6988 Artificial simulant standards for drone or FOD impact/ingestion	planned	SAE G-28 Simulants for Impact and Ingestion Testing	Dec-19	standard	planned	
M	Emergency recovery/terminations systems							ASTM WK59171 New Specification for sUAS parachutes	Develop a draft standard that defines the requirements for a parachute system that would allow an applicant/proponent to obtain approval to operate a small Unmanned Aircraft System (sUAS) directly over people.	ASTM F38 Unmanned Aircraft Systems	Mar-18	specification	ongoing	Will meet Jun 12-13 to adjudicate final comments
A	Emergency recovery/terminations systems							F3322-18 Standard Specification for Small Unmanned Aircraft System (sUAS) Parachutes	This specification covers the design and manufacture requirements for deployable parachutes of small unmanned aircraft (sUA). This specification defines the design, fabrication, and test requirements of installable, deployable parachute recovery systems (PRS) that are designed to be integrated into a sUA to lessen the impact energy of the system should the sUA fail to sustain normal stable safe flight. Compliance with this specification is intended to support an applicant in obtaining permission from a civil aviation authority (CAA) to fly a sUA over people.	ASTM F38 Unmanned Aircraft Systems	Sept-18	specification	Published	
	UA Design and Airworthiness							F2490-05(2013) Standard Guide for Aircraft Electrical Load and Power Source Capacity Analysis	This guide covers how to prepare an electrical load analysis (ELA) to meet Federal Aviation Administration (FAA) requirements.	ASTM F39 Aircraft Systems		standard	published	Light Sport Aircraft guidance will be revised to apply to UAS.
	maintenance							F2799-14 Standard Practice for Maintenance of Aircraft Electrical Wiring Systems	Damaged wiring or equipment in an aircraft, regardless of how minor it may appear to be, cannot be tolerated. It is, therefore, important that maintenance be accomplished using the best techniques and practices to minimize the possibility of failure.	ASTM F39 Aircraft Systems		standard	published	
M	UA Design and Airworthiness							ASTM WK62670 New Specification for Large UAS Design and Construction	To develop an ASTM design and construction standard for larger mass fixed wing Unmanned Aerial Systems (UAS). Design and Construct Standards are currently in existence for Part 23 General Manned Aircraft as well as for Fixed Wing and VTOL Small UAS (sUAS). There currently exists a gap for Part 23 General Aircraft of the Large Fixed Wing Unmanned Variety. This ASTM standard will serve to fill that gap by including design and construct requirements, best practices, and proposed methods of compliance specific to Large UAS (up to 19,000 lbs).	ASTM F38 Unmanned Aircraft Systems	Jun-19	standard	under development	

	UA Design and Airworthiness								ASTM F2910-14 Standard Specification for Design and Construction of a Small Unmanned Aircraft System (sUAS)	This specification establishes the design, construction, and test requirements for a small unmanned aircraft system (sUAS). It is intended for all sUAS that are permitted to operate over a defined area and in airspace authorized by a nation's governing aviation authority (GAA). Unless otherwise specified by a nation's GAA, this specification applies only to UA that have a maximum takeoff gross weight of 55 lb/25 kg or less.	ASTM F38 Unmanned Aircraft Systems		standard	published	This will be reference in AC for Special Class §21.17(b)	
M	UA Design and Airworthiness								F3298-18 Standard Specification for Design, Construction, and Verification of Fixed-Wing Unmanned Aircraft Systems (UAS)	This specification covers the airworthiness requirements for the design of fixed-wing unmanned aircraft systems. This specification defines the baseline design, construction, and verification requirements for an unmanned aircraft system (UAS)	ASTM F38 Unmanned Aircraft Systems		standard	published	Will be revised to include VTOL aircraft under ASTM WK64619/ WK64619	
M	UA Design and Airworthiness								ASTM WK63678/ WK64619 Revision of F3298 - 18 Standard Specification for Design, Construction, and Verification of Fixed-Wing Unmanned Aircraft Systems (UAS)	The initial standard only addressed Fixed-Wing UAS. Response from the FAA required both vertical lift and fixed-wing in order to be accepted as a method of compliance for UAS airworthiness certification in the forthcoming advisory circular for 21-17(b). This required a rapid-action reorganization of the standard, inclusion of VTOL-specific items and a title change.	ASTM F38 Unmanned Aircraft Systems	19-Nov	standard	In progress	Ballot pending Sub-Committee approval	
	Manufacturer organisation								ASTM F2911-14e1 Standard Practice for Production Acceptance of Small Unmanned Aircraft System (sUAS)	This standard defines the production acceptance requirements for a small unmanned aircraft system (sUAS). This standard is applicable to sUAS that comply with design, construction, and test requirements identified in Specification F2910. No sUAS may enter production until such compliance is demonstrated.	ASTM F38 Unmanned Aircraft Systems		standard	published		
	Manufacturer organisation								ASTM F3003-14 Standard Specification for Quality Assurance of a Small Unmanned Aircraft System (sUAS)	This standard defines the quality assurance requirements for the design, manufacture, and production of a small unmanned aircraft system (sUAS).	ASTM F38 Unmanned Aircraft Systems		standard	published		
	Batteries/fuel cell power generating system								WKWK6937 Standard Specification for design of Fuel Cells for Use in Unmanned Aircraft Systems (UAS)	This standard will outline specification for the use of fuel cell power generating systems for application in UAS.	ASTM F38 Unmanned Aircraft Systems	TBD	standard	ongoing		
	Development assurance (Software)								ASTM F3201-16 Standard Practice for Ensuring Dependability of Software Used in Unmanned Aircraft Systems (UAS)	This standard practice intends to ensure the dependability of UAS software. Dependability includes both the safety and security aspects of the software. This practice will focus on the following areas: (a) Organizational controls (for example, management, training) in place during software development, (b) Use of the software in the system, including its architecture and contribution to overall system safety and security; (c) Metrics and design analysis related to assessing the code; (d) Techniques and tools related to code review; (e) Quality assurance; (f) Testing of the software.	ASTM F38 Unmanned Aircraft Systems		standard	published		
M	UA Design and Airworthiness								ASTM WK16285 New Specification for Design and Performance of an Unmanned Aircraft System-Class 1320 (550# Gross Weight to 1320# Gross Weight)	The specification covers airworthiness requirements for an acceptable powered fixed wing aircraft UAS.	ASTM F38 Unmanned Aircraft Systems	TBD	standard	ongoing	This work item will be continued using guidelines from ASTM F37 Light Sport Aircraft Committee	
M	UA Design and Airworthiness								ASTM WK60352 Design, Construct, and Test of VTOL	This specification establishes the design, construction, and test requirements for a VTOL, unmanned aircraft system (sUAS). It is intended for all UAS that are permitted to operate over a defined area and in airspace authorized by a nation's governing aviation authority (GAA). Unless otherwise specified by a nation's GAA,	ASTM F38 Unmanned Aircraft Systems	Aug-18	standard	ongoing	Will be incorporated in F3298 - Draft complete	
M	UA Design and Airworthiness								ASTM WK57859 Design, Construction and Verification of Fixed Wing UAS	This specification establishes the design, construction, and test requirements for a fixed wing unmanned aircraft system (sUAS). It is intended for all UAS that are permitted to operate over a defined area and in airspace authorized by a nation's governing aviation authority (GAA). Unless otherwise specified by a nation's GAA,	ASTM F38 Unmanned Aircraft Systems		standard	approved		
A	Manuals								WK63407 Required Product Information to be Provided with a Small Unmanned Aircraft System	This specification covers the Unmanned Aircraft Flight Manual (UFM), Maintenance Manual, Aircraft Kit Assembly Instructions (KAI), Component Original Equipment Manufacturer (OEM) manuals, sUAS OEMs Statement of Compliance, and Airframe Records information required for aircraft designed and	ASTM F38 Unmanned Aircraft Systems	TBD	standard	ongoing		
	maintenance								ASTM F2909-14 Standard Practice for Maintenance and Continued Airworthiness of Small Unmanned Aircraft Systems (sUAS)	This standard is written for all sUAS that are permitted to operate over a defined area and in airspace authorized by a nation's governing aviation authority (GAA). It is assumed that a visual observer(s) will provide for the sense and avoid requirement to avoid collisions with other aircraft and that the maximum range and altitude at which the sUAS can be flown will be specified by the nation's GAA. Unless otherwise specified by a nation's GAA, this standard applies only to UA that have a maximum take off gross weight of 25 kg (55 lb) or less. The sUAS shall be maintained for continued airworthiness to meet sUAS limitations and performance capabilities required by the nation's GAA.	ASTM F38 Unmanned Aircraft Systems		standard	published	Updated revision underway	
M	UA Design and Airworthiness								Aerospace series - Unmanned Aircraft Systems (UAS) - Product requirements	To develop European standards specifying the means of compliance to the regulatory requirements defined in the Delegated act of the EASA Opinion No 01-2018. These standards define the design, construction and test requirements for CE marking conformity and covers topics such as: · Physical and mechanical properties, · Flammability, · Electrical properties, · Functional Safety · Sound · Navigation lights	ASD-STAN D5WG8	Dec-2019	European standard	planned		
	Ground control station								MASPS	Minimum Aviation System Performance Standard (End-to-end Requirements at system level) for the Remote Pilot Station interface to Air Traffic Control (ATC).	EUROCAE WG-105	Jun-19	standard	ongoing		
	UA Design and Airworthiness	Opinion No.1 2018	Appendix 1, 2, 3, 4 to delegated act A UAS Class C0, C1, C2 and C3 shall have a maximum attainable height above the take-off point limited to 120 m or be equipped with a system that limits the height above the surface or above the take-off point to a value selectable by the remote pilot; in the latter case, clear information about the height of the UA above the surface or take-off point during flight shall be provided to the remote pilot;	EASA	Mar-19	open	Opinion published									
	UA Design and Airworthiness	Opinion No.1 2018	Appendix 1, 2 to delegated act A UAS Class C0 and C1 shall (3) if equipped with a follow-me mode, when this function is on, keep a distance not exceeding 50 m from the remote pilot, and allow the remote pilot to regain control of the UA or to activate an emergency procedure that terminates the flight;	EASA	Mar-19	open	Opinion published									
	Manufacturer organisation								ISO 21384-2 - Requirements for ensuring the quality and safety of the design and manufacture of UAS. It includes information regarding the UA, any associated remote control station(s), the C2 links, any other required data links and any other system elements as may be required.		ISO TC20/SC16/WG2	Dec-17	standard	ongoing		
	UA Design and Airworthiness								STANAG 4671 "UAV System Airworthiness Requirements (USART) - (Fixed wing UAV, MTOW<150kg)	Set of technical airworthiness requirements intended primarily for the airworthiness certification of fixed-wing military UAS with a maximum take-off weight between 150 and 20,000 kg that intend to regularly operate in non-segregated airspace	NATO FINAS			published		
	UA Design and Airworthiness								STANAG 4702 "Rotary Wing Unmanned Aerial Systems Airworthiness Requirements" (Rotorcraft UAV, 150Kg-MTOW<1125Kg)	set of technical airworthiness requirements intended for the airworthiness certification of rotary-wing military UAV systems with a maximum take-off weight between 150 and 1175 kg that intend to regularly operate in non-segregated airspace	NATO FINAS			published		

M	Automatic modes, takeoff, Landing, taxiing								WK58931 Evaluating AerialResponse RobotManeuvering: Maintain Position and Orientation	The purpose of this test method is to specify the apparatuses, procedures, and performance metrics necessary to quantitatively evaluate the system capability to accurately maintain position and orientation (pose) in open space relative to an object of interest. This test method applies to aerial systems operated remotely from a standoff distance appropriate for the intended mission. The system includes a remote operator in control of all functionality and any assistive features or autonomous behaviors that improve the effectiveness or efficiency of the overall system. This test method may be performed anywhere the specified apparatuses and environmental conditions can be implemented as described. Results should be considered within the context of related test methods in the Maneuvering suite when comprehensively evaluating robotic system capabilities.	ASTM E54 Homeland Security Applications	TBD	standard	ongoing	E54 Full Committee adjudication February 26 to March 2, 2018. Delayed till Apr-18
M	Automatic modes, takeoff, Landing, taxiing								WK58932 Evaluating AerialResponse RobotManeuvering: Orbit a Point	The purpose of this test method is to specify the apparatuses, procedures, and performance metrics necessary to quantitatively evaluate the system capability to accurately orbit an object of interest. Results should be considered within the context of related test methods in the Maneuvering suite when comprehensively evaluating robotic system capabilities. This test method applies to aerial systems operated remotely from a standoff distance appropriate for the intended mission. The system includes a remote operator in control of all functionality and any assistive features or autonomous behaviors that improve the effectiveness or efficiency of the overall system. This test method may be performed anywhere the specified apparatuses and environmental conditions can be implemented as described.	ASTM E54 Homeland Security Applications	TBD	standard	ongoing	
M	Detect and avoid								WK58933 Evaluating AerialResponse RobotManeuvering: Avoid Static Obstacles	The purpose of this test method is to specify the apparatuses, procedures, and performance metrics necessary to quantitatively evaluate the system capability to avoid static obstacles.	ASTM E54 Homeland Security Applications	TBD	standard	ongoing	E54 Full Committee adjudication February 26 to March 2, 2018. Delayed till Apr-18
M	Detect and avoid								WK58934 Evaluating AerialResponse RobotManeuvering: Pass Through Openings	The purpose of this test method is to specify the apparatuses, procedures, and performance metrics necessary to quantitatively evaluate the system capability to pass through openings of various sizes and orientations.	ASTM E54 Homeland Security Applications	TBD	standard	ongoing	E54 Full Committee adjudication February 26 to March 2, 2018. Delayed till Apr-18
M	Automatic modes, takeoff, Landing, taxiing								WK58935 Evaluating AerialResponse RobotManeuvering: Land Accurately (Vertical)	The purpose of this test method is to specify the apparatuses, procedures, and performance metrics necessary to quantitatively evaluate the system capability to accurately land vertically within a defined area.	ASTM E54 Homeland Security Applications	TBD	standard	ongoing	E54 Full Committee adjudication February 26 to March 2, 2018. Delayed till Apr-18
	UAS-ATM								Specifications for the Use of Military Unmanned Aerial Vehicles (UAV) as Operational Air Traffic (OAT) outside segregated airspace specification, v 1.0, 2007	This specification addresses aspects of military UAV ATM, dealing briefly with extant regulations that impact upon the UAV specifications and then explaining the nature of UAV airspace requirements. It also summarizes a number of national UAV ATM regulations, albeit none were suitable for adaptation into EUROCONTROL specifications	EUROCONTROL		specification	published	
	UAS-ATM								Air Traffic Management Guidelines for Global Hawk in European Airspace, v 1.0, 2010	These Guidelines establish a set of minimum ATM requirements for Global Hawk (GH) (Euro Hawk EHI) flight in European airspace, with the primary purpose of enabling GHEH operators to use them as the basis for negotiating access to national airspace within Europe. The Guidelines envisage the isolation of GHEH from other airspace users by requiring it to climb-out and recover in segregated airspace and to fly IFR/OAT in the cruise in non-segregated airspace at high altitudes that are above those occupied by manned aviation.	EUROCONTROL		guidance material	published	
	Local E-identification								Aerospace series - Unmanned Aircraft Systems (UAS) - Security requirements	To develop European standards specifying the means of compliance to the regulatory requirements defined in the Delegated act of the EASA Opinion No 01-2018. This activity shall be coordinated with EUROCAE WG105 (SG-32 and SG-33) and it will intend to address at least the following topics: "See-awariness" function for UA Operations which includes Airspace areas, Qualification of the UA operator, relevant authorization, prohibited area, identification of special zones (ref. level U1 U-Space) "e-ID" Electronic Identification, means the capability to identify a UA in flight without direct physical access to that aircraft (only for local identification from the ground)	ASD-STAN DSWG8	Dec-19	European standard	planned	
	Standard scenarios								ASTM F3196-17 Standard Practice for Seeking Approval for Extended Visual Line of Sight (EVLOS) or Beyond Visual Line of Sight (BVLOS) Small Unmanned Aircraft System (sUAS) Operations	Compliance with this practice is recommended as one means of seeking approval from a civil aviation authority (CAA) to operate a small unmanned aircraft system (sUAS) to fly extended visual line of sight (EVLOS) or beyond visual line of sight (BVLOS), or both. Any regulatory application of this practice to sUAS and other unmanned aircraft systems (UASs) is at the discretion of the appropriate CAA.	ASTM F38 Unmanned Aircraft Systems		standard	published	To be revised and amended to include use case scenarios: package delivery, infrastructure inspection, linear inspection, search and rescue, emergency response, terminal operations, agriculture. First of these spendices (package delivery) to be completed Jun 2018. Final available but revisions to standard will be incorporated in Jan 2018 after Pathfinder Technical Interchange
	Standard scenarios								ASTM WK60746 Standard Practice for Seeking Approval for Extended Visual Line of Sight (EVLOS) or Beyond Visual Line of Sight (BVLOS) Small Unmanned Aircraft System (sUAS) Operations	The main purpose of this revision is to add an Appendix A that provides research findings from the FAA EVLOS Pathfinder program than can be used in developing proposed risk mitigation strategies for sUAS EVLOS operations. This revision also provides a reference to Unmanned Systems Canada Best Practices for BVLOS Operations for use in developing proposed risk mitigation strategies for both EVLOS and BVLOS operations.	ASTM F38 Unmanned Aircraft Systems	Jun-18	standard	ongoing	Revisions to F3196 being finalized.
	Standard scenarios								ASTM WK 62344 BVLOS Package Delivery as an Appendix to F3196-17	Appendix to ASTM F3196-17. The main purpose of this revision is to add an Appendix that can be used in developing proposed risk mitigation strategies for package delivery sUAS BVLOS operation	ASTM F38 Unmanned Aircraft Systems	Jun-19	standard	ongoing	Working group formed
	Operations								ASTM F2849-10 Standard Practice for Handling of Unmanned Aircraft Systems at Divert Airfields		ASTM F38 Unmanned Aircraft Systems		practice	published	
	Operations								ISO 21384-3 - Requirements for safe civil RPAS/UAS operations and applies to all types, categories, classes, sizes and modes of operation of UAS	Requirements for safe commercial UAS operations and applies to all types, categories, classes, sizes and modes of operation of UAS.	ISO	Dec-18	standard	ongoing	
	UAS-ATM								ARP#### Access to controlled airspace		SAE G-30 UAS Operator Qualifications Committee	May-19	recommended practice	planned	
	Standard scenarios								ARP#### Flight beyond visual line of sight		SAE G-30 UAS Operator Qualifications Committee	May-19	recommended practice	planned	
	Standard scenarios								ARP#### Night operations		SAE G-30 UAS Operator Qualifications Committee	May-19	recommended practice	planned	

	Standard scenarios							ARP### Aerial photography		SAE G-30 UAS Operator Qualifications Committee	Jun-19	recommended practice	planned	
	Standard scenarios							ARP### Power line inspection		SAE G-30 UAS Operator Qualifications Committee	Jul-19	recommended practice	planned	
	Standard scenarios							ARP### Precision agriculture		SAE G-30 UAS Operator Qualifications Committee	Aug-19	recommended practice	planned	
	Standard scenarios							ARP### Bridge inspection		SAE G-30 UAS Operator Qualifications Committee	Sep-19	recommended practice	planned	
	Standard scenarios							ARP### Train right-of-way's		SAE G-30 UAS Operator Qualifications Committee	Oct-19	recommended practice	planned	
	Standard scenarios							ARP### Flare stack inspections		SAE G-30 UAS Operator Qualifications Committee	Nov-19	recommended practice	planned	
	Standard scenarios							WKS8243 New Guide for Visual Inspection of Building Facade using Drone	This standard consists of guidelines for utilizing drones with cameras to document facade conditions with video and still photography. The purpose of this standard is to establish procedures and methodologies for conducting visual inspections of building facades via drone, and documenting such inspections.	ASTM E06 Performance of Buildings	Jan-18	guide	ongoing	
	Navigation							WKS8677 Evaluating AerialResponse RobotSensing: Visual Image Acuity	The purpose of this test method is to specify the apparatuses, procedures, and performance metrics necessary to quantitatively evaluate the visual (electro-optical) image acuity of the system as viewed through a control station. This test method applies to aerial systems operated remotely from a standoff distance appropriate for the intended mission. The system includes a remote operator in control of all functionality and any assistive features or autonomous behaviors that improve the effectiveness or efficiency of the overall system. This test method may be performed anywhere the specified apparatuses and environmental conditions can be implemented as described. Results should be considered within the context of related test methods in the Maneuvering suite when comprehensively evaluating robotic system capabilities.	ASTM E54 Homeland Security Applications	Apr-18	standard	ongoing	E54 Full Committee adjudication February 26 to March 2, 2018. Delayed till Apr-18
	Ground control station							WKS8925 Evaluating AerialResponse RobotSensing: Visual Color Acuity	The purpose of this test method is to specify the apparatuses, procedures, and performance metrics necessary to quantitatively evaluate the visual (electro-optical) color acuity of the system as viewed through a control station.	ASTM E54 Homeland Security Applications	Apr-18	standard	ongoing	E54 Full Committee adjudication February 26 to March 2, 2018. Delayed till Apr-18
	Ground control station							WKS8926 Evaluating AerialResponse RobotSensing: Visual Dynamic Range	The purpose of this test method is to specify the apparatuses, procedures, and performance metrics necessary to quantitatively evaluate the visual (electro-optical) dynamic range of the system as viewed through a control station.	ASTM E54 Homeland Security Applications	Apr-18	standard	ongoing	E54 Full Committee adjudication February 26 to March 2, 2018. Delayed till Apr-18
	C3 datalink and communication							WKS8927 Evaluating AerialResponse RobotSensing: Audio Speech Acuity	The purpose of this test method is to specify the apparatuses, procedures, and performance metrics necessary to quantitatively evaluate the audio speech acuity of the system as heard bi-directionally between a control station and aerial robot in flight.	ASTM E54 Homeland Security Applications	Apr-18	standard	ongoing	E54 Full Committee adjudication February 26 to March 2, 2018. Delayed till Apr-18
	Ground control station							WKS8928 Evaluating AerialResponse RobotSensing: Thermal Image Acuity	The purpose of this test method is to specify the apparatuses, procedures, and performance metrics necessary to quantitatively evaluate the thermal image acuity of the system as viewed through a control station. This test method applies to aerial systems operated remotely from a standoff distance appropriate for the intended mission.	ASTM E54 Homeland Security Applications	Apr-18	standard	ongoing	E54 Full Committee adjudication February 26 to March 2, 2018. Delayed till Apr-18
	Ground control station							WKS8929 Evaluating AerialResponse RobotSensing: Thermal Dynamic Range	The purpose of this test method is to specify the apparatuses, procedures, and performance metrics necessary to quantitatively evaluate the thermal dynamic range of the system as viewed through a control station.	ASTM E54 Homeland Security Applications	Apr-18	standard	ongoing	E54 Full Committee adjudication February 26 to March 2, 2018. Delayed till Apr-18
	Ground control station							WKS8930 Evaluating AerialResponse RobotSensing: Latency of Video, Audio, and Control	The purpose of this test method is to specify the apparatuses, procedures, and performance metrics necessary to quantitatively evaluate the latency of video, audio, and control sub-systems as viewed through a control station.	ASTM E54 Homeland Security Applications	Apr-18	standard	ongoing	E54 Full Committee adjudication February 26 to March 2, 2018. Delayed till Apr-18
	Detect and avoid							WKS8936 Evaluating AerialResponse RobotSituational Awareness: Identify Objects (Point and Zoom Cameras)	The purpose of this test method is to specify the apparatuses, procedures, and performance metrics necessary to quantitatively evaluate the system capability to identify objects of interest in the environment using cameras (electro-optical and thermal) from defined altitudes in open space.	ASTM E54 Homeland Security Applications	Apr-18	standard	ongoing	E54 Full Committee adjudication February 26 to March 2, 2018. Delayed till Apr-18
	Standard scenarios							WKS8937 Evaluating AerialResponse RobotSituational Awareness: Inspect Static Objects	The purpose of this test method is to specify the apparatuses, procedures, and performance metrics necessary to quantitatively evaluate the system capability to inspect objects of interest in close proximity.	ASTM E54 Homeland Security Applications	Apr-18	standard	ongoing	E54 Full Committee adjudication February 26 to March 2, 2018. Delayed till Apr-18
	Standard scenarios							WKS8938 Evaluating AerialResponse RobotSituational Awareness: Map Wide Areas (Stitched Images)	The purpose of this test method is to specify the apparatuses, procedures, and performance metrics necessary to quantitatively evaluate the system capability to accurately map wide areas with objects of interest in the environment.	ASTM E54 Homeland Security Applications	Apr-18	standard	ongoing	E54 Full Committee adjudication February 26 to March 2, 2018. Delayed till Apr-18
	Standard scenarios							ASTM WKS2858 Small Unmanned Aircraft Systems (sUAS) for Land Search and Rescue	This classification defines small unmanned aircraft system (sUAS) land search and rescue resources in terms of their capabilities. It provides a means by which resource managers and sUAS pilots/operators can convey to emergency management the tasks for which their systems are capable of performing.	ASTM F32 Search and Rescue	TBD	standard	ongoing	
	Standard scenarios							ASTM WKS4226 sUAS Operations in Search and Rescue Operations	This guide establishes a framework within which sUAS search and rescue (SAR) operations shall be conducted as part of the National Incident Management System (NIMS)/Incident Command System (ICS). 1.2 The requirements of this guide shall apply to individuals, agencies, and organizations that respond to SAR operations, including those not regulated by government mandates.	ASTM F32 Search and Rescue	TBD	standard	ongoing	
M	Standard scenarios							ASTM WKS2089 New Specification for Operation over People	Recent research conducted on risk, safety, design, operations and impact to inform development of standard with supporting documentation from Pathfinder studies. Using results of the Pathfinder Program, impact testing and mitigations such as deployable sUAS parachutes to be incorporated into standard.	ASTM F38 Unmanned Aircraft Systems	Mar-19	specification	ongoing	Final draft for ballot in October 2018
M	UA Design and Airworthiness							ASTM WKS6338 Safety of Unmanned Aircraft Systems for Flying Over People	Develop a draft standard for product marking of UAS weighing 250 grams or less. Develop draft standard for Category 2, 3, and 4 UAS that: (1) Establishes a test method(s) to measure typical or likely impact energy of the small unmanned aircraft when the aircraft is operating in the most probable failure mode(s) to determine whether it meets the FAA specified impact energy threshold. Testing may be subject to manufacturer defined operating limitations, if any. The impact energy threshold used in the standards may account for the energy dissipation caused by the physical design of the small unmanned aircraft and likely impact scenarios.	ASTM F38 Unmanned Aircraft Systems	TBD	standard	ongoing	Adjudicating ballot comments
M	Risk Assessment							ASTM F3176-16 Standard Practice for Operational Risk Assessment of Small Unmanned Aircraft Systems (sUAS)	Preparation of an ORA in accordance with this practice is intended to reduce, the risk of an operation in which system complexity is minimal, the operation is conducted in a lower risk environment, and the likelihood for harm to people or property, though present, is reduced to an acceptable level. As mission complexity increases, the operational environment may become less risk tolerant.	ASTM F38 Unmanned Aircraft Systems		standard	published	This will be reference in AC for Special Class §21.17(b)
M	Manuals							ASTM WK6938 New Practice for General Operations Manual for Professional Operator of Light Unmanned Aircraft Systems (UAS)	This standard defines the requirements for General Operations Manual for Professional Operator of Light Unmanned Aircraft Systems (UAS). The standard addresses the requirements and/or best practices for documentation and organization of a professional operator (i.e., for compensation and here).	ASTM F38 Unmanned Aircraft Systems	Sep-18	specification	ongoing	Draft Complete -will be balloted Jun 2018

	Take off/ Landing zones							ASTM WK6317 Vertipod Design	To support the design of civil vertiports and vertistops for the landing and takeoff of VTOL aircraft boarding and discharging passengers or cargo. The proliferation of electric-powered VTOL should be carefully considered in the development of this document. The standard must be scalable to address aircraft ranging in size and kinetic energy, including unmanned and optionally piloted aircraft.	ASTM F38 Unmanned Aircraft Systems	TBD	specification	ongoing	New draft in work
	UAS-ATM							STANAG 7234 Remotely Piloted Aircraft Systems (RPAS) Airspace Integration (AI) - AATMP-51		NATO FINAS	2018	standard	ongoing	Under development
	C3 datalink and communication							STANAG 7232 Unmanned Aerial Systems Tactics Techniques and Procedures - ATP-3.3.8.2 Edition A	Provide standardized tactics, techniques, and procedures 217 for the planning, command and control (C2), and employment of unmanned aircraft systems 218 (UAS) in NATO operations	NATO MCASBUJGUAS OS	2018	standard	ongoing	Under development
8 FCL														
	Remote pilot competence	Opinion No.1 2018	UAS.OPEN.50 and UAS.OPEN.50 by a remote pilot who holds a certificate of remote pilot competency that is necessary to ensure a safe flight, respecting privacy, data protection, security and environmental requirements, by passing a theoretical test in a manner and format established by EASA at an entity recognised by the competent authority; and	EASA	Mar-19	open and specific	Opinion published							
	Remote pilot competence							ARPS707 - Pilot Training Recommendations for Unmanned Aircraft Systems (UAS) Civil Operations	This document provides an approach to the development of training topics for pilots of Unmanned Aircraft Systems (UAS) for use by operators, manufacturers, and regulators. The identification of training topics is based initially on Practical Test Standard (PTS) topics for manned aircraft pilots. The topics identified could be used for the construction of a PTS for UAS commercial pilot operations and a PTS for a UAS pilot instrument rating. The UAS commercial pilot rating would contain restrictions on the types of operations that could be flown that would be dependent on the type of UAS used. The UAS type would also influence the specific training topics that would be covered. This document is not intended to outline the requirements for other crewmembers, such as observers, payload operators or ground personnel, nor does it distinguish between different levels of pilot authority or discuss the roles for pilot-in-command, supplemental pilot, or observer.	SAE G-30 UAS Operator Qualifications Committee & G-10U Unmanned Aerospace Vehicle Committee		recommended practice	published	
	Remote pilot competence							ARF### Common operator qualifications		SAE G-30 UAS Operator Qualifications Committee	May-19	recommended practice	planned	
	Remote pilot competence	Opinion No.1 2018	UAS.OPEN.040 by a remote pilot who has demonstrated the competencies necessary to ensure a safe flight, respecting privacy, data protection, security and environmental requirements, by having completed an online training course and passed an online test, according to a manner and format established by EASA, and provided by an entity recognised by the competent authority.	EASA	Mar-19	open and specific	Opinion published							
	maintenance							ASTM WK60659 UAS Maintenance Technician Qualification	Will outline qualifications required for skilled UAS maintenance technicians with broad understanding of supporting the continued airworthiness of UAS platforms and their subsystems.	ASTM F38 Unmanned Aircraft Systems	Jun-18	standard	ongoing	Undergoing revisions prior to ballot
	Remote pilot competence							WK61764 Training for Public Safety Remote Pilot of UAS Endorsement	To develop a standard that defines the requirements for Training for Public Safety Remote Pilot of Unmanned Aircraft Systems (UAS) Endorsement. The guide describes the knowledge, skills, and abilities required to operate unmanned aircraft for public safety purposes. A CAA may, at their discretion, use this guide to aid the development of regulations. An approved ASTM guide that describes required education, training, and continuing professional development for those performing as professional	ASTM F38 Unmanned Aircraft Systems	TBD	standard	ongoing	
	Remote pilot competence							ASTM F3266 Standard Guide for Training and Certification of sUAS Pilots, Instructors, and School Houses	Establish criteria for Training and Certification of sUAS Pilots, Instructors, and School Houses. This practice defines the knowledge, skills, and abilities sUAS pilots require for the conduct training and flight operations for Small Unmanned Aircraft Systems (sUAS) in the NAS. The Training and Certification of sUAS Pilots, Instructors, and School Houses include areas to cover pilot qualifications, training and proficiency, instructor certification, and sUAS flight training facility operations. This document sets forth standards to meet the requirements to establish quality training and certification programs, and facilitate aviation safety.	ASTM F38 Unmanned Aircraft Systems	Apr-18	standard	published	
D	Remote pilot competence							ASTM WK29229 New Practice for Certification of Pilots, Visual Observers, and Instructor Pilots and Training courses for Small Unmanned Aircraft Systems (sUAS)						It has been published as F3266 in line 235
	Remote pilot competence							ARPS707 Pilot Training Recommendations for Unmanned Aircraft Systems (UAS) Civil Operations	This document provides an approach to the development of training topics for pilots of Unmanned Aircraft Systems (UAS) for use by operators, manufacturers, and regulators. The identification of training topics is based initially on Practical Test Standard (PTS) topics for manned aircraft pilots. The topics identified could be used for the construction of a PTS for UAS commercial pilot operations and a PTS for a UAS pilot instrument rating. The UAS commercial pilot rating would contain restrictions on the types of operations that could be flown that would be dependent on the type of UAS used.	G-30 UAS Operator Qualifications Committee & G-10U Unmanned Aerospace Vehicle Committee		recommended practice	published	
	Remote pilot competence							STANAG 7192 Ed: 1 Principles Underpinning Medical Standards for Operators of Unmanned Aerial Systems (UAS) - AAMedP-1.25, Edition A	Highlight the medical factors involved in the medical aspects of Flight Crew Licensing to enable individual nations to further their own medical standards for safe UAS operation.	NATO		standard	published	
	Remote pilot competence	EASA Decision	OSD #09 - Remote crew trained and current and able to control the abnormal and emergency situations (i.e. Technical issue with the UAS)	EASA	May-19	Specific	ongoing							
	Remote pilot competence	EASA Decision	OSD #15 - Remote crew trained and current and able to control the abnormal and emergency situations (i.e. Human Error)	EASA	May-19	Specific	ongoing							
	Remote pilot competence	EASA Decision	OSD #22 - The remote crew is trained to identify critical environmental conditions and to avoid them	EASA	May-19	Specific	ongoing							
	Remote pilot competence	EASA Decision	OSD#16 Multi crew coordination. (Criterion #2 Training)	EASA	May-19	Specific	ongoing							
	Remote pilot competence	EASA Decision	OSD#17 Remote crew is fit for the operation	EASA	May-19	Specific	ongoing							

	Remove pilot competence	EASA Decision	050#19 Safe recovery from Human Error (<u>Criterion #2 Training</u>)	EASA	May-19	Specific	ongoing										
	Remove pilot competence	EASA Decision	050#23 Environmental conditions for safe operations defined, measurable and adhered to (<u>Criterion #1 Procedures</u>)	EASA	May-19	Specific	ongoing										
	Remove pilot competence	EASA Decision	M#1 An Emergency Response Plan (ERP) is in place, operator validated and effective (<u>Criterion #2 Remote Crew Competence</u>)	EASA	May-19	Specific	ongoing										
9 Environment																	
	Noise&Environment	Opinion No.1 2018	Appendix 2, 3 to Delegated Act UAS in class C2 and C3 shall have a sound pressure level not exceeding 60 dB(A) (measured at a 3-m distance from the UA);	EASA	Mar-19	open	Opinion published										
10 Autonomous operations																	
	Autonomous operations							AS6386 JAUS Autonomous Behaviors Service Set	This document, the JAUS Automated Behaviors and Diagnostics Service Set, defines a message-passing interface for services commonly found in mobile unmanned systems. These services represent the platform-independent capabilities common across all domains. Additional capabilities are specified in the JAUS Core Service Set (AS5710) and are frequently referenced herein.	SAE AS-4JAUS Joint Architecture for Unmanned Systems Committee	May-19	standard	ongoing				
	Autonomous operations							ASTM Aviation Autonomy Roadmap	Task group to matrix autonomy technologies and standards between manned and unmanned aircraft.	ASTM	TBD	standards and practices	ongoing	Task Group Formed			
	Development assurance (Software)							ASTM F3269 Standard Practice for Methods to Safely Bound Flight Behavior of Unmanned Aircraft Systems Containing Complex Functions	This standard practice defines design and test best practices that if followed would provide guidance to an applicant for providing evidence to the civil aviation authority (CAA) that the flight behavior of an unmanned aircraft system (UAS) containing complex function(s) is constrained through a runtime assurance (RTA) architecture to maintain an acceptable level of flight safety.	ASTM F36 Unmanned Aircraft Systems Committee		standard	published				
	Autonomous operations							AS8024 JAUS Autonomous Behaviors Service Set	This document, the JAUS Automated Behaviors and Diagnostics Service Set, defines a message-passing interface for services commonly found in mobile unmanned systems. These services represent the platform-independent capabilities common across all domains. Additional capabilities are specified in the JAUS Core Service Set (AS5710) and are frequently referenced herein.	SAE AS-4JAUS Joint Architecture for Unmanned Systems Committee	May-19	standard	ongoing	The title will change to "JAUS Autonomous Capabilities Service Set"			